



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 04/08/16'	~	

- Specifications:
- 1.Current Rating: 60A Maximum.
  - 2.Voltage Rating: 320V
  - 3.Contact Resistance: 10m Ω/30mm max.
  - 4.All Dimensions By Customer Specify.
  - 5.Temperature Range: -55~+125 ℃.
  - 6.Plating: Full Tin or Full Gold(50u" Maximum).
  - 7.Resistance to Soldering Heat: 260 ±5 ℃,3~5 seconds.
  - 8.RoHS2.0 & REACH Compliance.
  - 9.Packing Type: PE Bag + Inner Box + Outer Box.
  - 10.Fit to PCB Thickness: 0.6 ~ 6.0mm.
- Product Number Code:

DS1143-01 - X X X X - X

- Dim. A B C D H T TYPE  
1:1.5/B2.5/C3.0/D3.0/H12/T1  
.....
- No. of Stairs  
2 3 .....
- Mounting type  
V: V/T
- Contact plating  
6: Full Tin  
8: Full Gold  
N: Full Nickel
- Connector type  
P:Pulg

Tel:86-574-63508787  
 Fax:86-574-63510817  
 E-mail:sale@connfly.com  
 http://www.connfly.com  
 Add:East Industry Zone KuangYan  
 Town Cixi Ningbo China  
 P.C:315333

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

PROJECTION		TITLE	PCB To PCB Copper Cylinder Series
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1143-01 SERIES

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1143-01-XXXX-X-A		

晨翔电子有限公司  
 CONNFLY CONNFLY ELECTRONIC CO. LTD